

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-5. (Canceled)

6. (Currently Amended) A system for mounting a device from the underside of a body having a planar surface, comprising:

a mounting bracket for attachment to an underside of a body having a planar surface
~~coupled to the planar surface of the underside of the body;~~

a tilt block rotatably coupled to the mounting bracket, the tilt block rotatable about a first axis substantially perpendicular to the mounting bracket~~planar surface~~;

a mounting arm rotatably coupled the tilt block, the mounting arm rotatable about a second axis substantially parallel to the mounting bracket ~~planar surface~~, the mounting arm having a single longitudinal axis;

an adapter slidably, movably and operatively connected to the mounting arm, the adapter configured to accept a display device for mounting thereon; and

a plurality of bearings for aiding the rotation of the tilt block relative the mounting bracket,

wherein the adapter is configured to slide towards and away from the tilt block along the longitudinal axis of the mounting arm.

7. (Original) The system of claim 6, wherein the plurality of bearings comprise first and second needle bearings, the first and second needle bearings positioned on opposite sides of the mounting bracket.

8. (Canceled)

9. (Canceled)

10. (Currently Amended) ~~The system of claim 9,~~ A system for mounting a device from the underside of a body having a planar surface, comprising:

a mounting bracket for attachment to an underside of a body having a planar surface;

a tilt block rotatably coupled to the mounting bracket, the tilt block rotatable about a first axis substantially perpendicular to the mounting bracket;

a mounting arm having a single longitudinal axis and rotatably coupled with the tilt block, the mounting arm rotatable about a second axis substantially parallel to the mounting;

an adapter movably and operatively connected to the mounting arm, the adapter configured to accept a display device for mounting thereon; and

means for sliding the adapter, connected to the mounting arm, along the longitudinal axis of the mounting arm,

wherein the sliding means comprises:

at least one elongate track positioned on the mounting arm parallel with the single longitudinal axis; and

at least one adapter arm positioned on the adapter for accepting the at least one elongate track, wherein the at least one adapter arm is slidable along the at least one elongate track;

wherein the at least one elongate track comprises two substantially parallel elongate tracks extending along substantially the entire length of the mounting arm, and wherein the at least one adapter arm comprises two substantially parallel adapter arms.

11. (Original) The system of claim 10, further comprising a cover piece coupled to the mounting arm, the cover piece and mounting bracket arranged to allow the passage of a cord therethrough.

12. (Currently Amended) A system for mounting a device from the underside of a body having a planar surface, comprising:

a mounting bracket for attachment to an underside of a body having a planar surface~~coupled to the planar surface of the underside of the body;~~

a tilt block rotatably coupled to the mounting bracket, the tilt block rotatable about a first axis substantially perpendicular to the mounting bracket~~planar surface~~;

a mounting arm having a single longitudinal axis and rotatably coupled with the tilt block, the mounting arm rotatable about a second axis substantially parallel to the mounting bracket~~planar surface~~;

an adapter movably and operatively connected to the mounting arm, the adapter configured to accept a display device for mounting thereon;

means for sliding the adapter, connected to the mounting arm, along the longitudinal axis of the mounting arm; and

a plurality of bearings for aiding the rotation of the tilt block relative the mounting bracket.

13. (Original) The system of claim 12, wherein the plurality of bearings comprise first and second needle bearings, the first and second needle bearings positioned on opposite sides of the mounting bracket.

14. (Currently Amended) The system of claim 12 ~~[[9]]~~, wherein the mounting bracket includes:

a lateral surface extending substantially parallel to the planar surface; and

a region between the lateral surface and ~~[[a]]~~ the planar surface for accepting a power source for the device.

15. (Canceled)

16. (Canceled)

17. (Currently Amended) The system of claim 16, further comprising: A system for mounting a display device from the underside of a body having a planar surface, comprising:

a mounting bracket for attachment to an underside of a body having a planar surface and including a region therein;

a tilt block rotatably coupled to the mounting bracket, the tilt block rotatable about a first axis of rotation substantially perpendicular to the mounting bracket;

a mounting arm rotatably coupled the tilt block, the mounting arm having a single longitudinal axis and rotatable about a second axis of rotation substantially parallel to the mounting bracket;

a cover piece coupled to the mounting arm, the cover piece and mounting bracket arranged to allow the passage of a cord therethrough;

an adapter movably and operatively connected to the mounting arm, the adaptor slidable along the single longitudinal axis of the mounting arm and the adapter configured to accept the display device for mounting thereon;

a first bearing system positioned between the mounting bracket and the tilt block; and

a second bearing system positioned between the mounting bracket and the planar surface, wherein the first bearing system and the second bearing system cooperate to permit the tilt block to rotate about the axis substantially perpendicular to the mounting bracket planar surface.

18. (Currently Amended) The system of claim 17 [[16]], further comprising a mounting bracket plate removably connected to mounting bracket, the mounting bracket plate positioned between the planar surface and the region.

19. (Original) The system of claim 18, further comprising:

at least one elongate track positioned on the mounting arm; and

at least one adapter arm positioned on the adapter for accepting the at least one elongate track, wherein the at least one adapter arm is slidable along the at least one elongate track.

20. (Currently Amended) The system of claim 17 [[16]], wherein the at least one elongate track comprises two substantially parallel elongate tracks extending along substantially the entire length of the mounting arm, and wherein the at least one adapter arm comprises two substantially parallel adapter arms.